



Cable ID: UTP CAT5e PVC LCU5-11CU-0305-S

Date / Time: 07/11/2019 08:46:37 AM

Headroom 7.2 dB (NEXT 12-78)

Test Limit: TIA Cat 5e Channel

Cable Type: Cat 5e U/UTP

NVP: 69.0%

Operator: JXT

Software Version: 2.7800

Limits Version: 1.9500

Calibration Date:

Main (Tester): 08/30/2012

Remote (Tester): 08/30/2012

Test Summary: PASS

Model: DTX-1800


Main S/N: 2156539

Remote S/N: 2156540

Main Adapter: DTX-CHA002



Remote Adapter: DTX-CHA002

Length (ft), Limit 328	[Pair 78]	324
Prop. Delay (ns), Limit 555	[Pair 45]	491
Delay Skew (ns), Limit 50	[Pair 45]	13
Resistance (ohms)	[Pair 36]	19.0
Insertion Loss Margin (dB)	[Pair 45]	3.6
Frequency (MHz)	[Pair 45]	100.0
Limit (dB)	[Pair 45]	24.0





Wire Map (T568B)

PASS





Worst Case Margin Worst Case Value



PASS	MAIN	SR	MAIN	SR
Worst Pair	12-78	12-78	36-78	12-78
NEXT (dB)	7.2	7.5	13.4	12.4
Freq. (MHz)	22.9	23.0	93.0	82.8
Limit (dB)	41.0	41.0	30.6	31.5
Worst Pair	12	12	78	78
PS NEXT (dB)	9.5	10.3	14.1	13.3
Freq. (MHz)	22.9	23.0	93.0	82.8
Limit (dB)	38.0	38.0	27.6	28.5





PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45	36-45	12-78	78-12
ACR-F (dB)	12.1	12.1	12.7	12.8
Freq. (MHz)	7.9	7.6	92.3	92.0
Limit (dB)	39.5	39.8	18.1	18.1
Worst Pair	45	12	12	12
PS ACR-F (dB)	12.3	12.3	13.8	14.3
Freq. (MHz)	7.9	59.8	86.3	91.8
Limit (dB)	36.5	18.9	15.7	15.1



N/A	MAIN	SR	MAIN	SR
Worst Pair	12-78	12-78	36-78	36-45
ACR-N (dB)	8.9	9.3	17.6	17.8
Freq. (MHz)	22.9	22.9	93.0	97.0
Limit (dB)	30.1	30.1	7.5	6.7
Worst Pair	12	12	78	36
PS ACR-N (dB)	10.5	11.7	18.2	19.5
Freq. (MHz)	7.4	1.6	93.3	97.3
Limit (dB)	40.1	53.9	4.5	3.6



PASS	MAIN	SR	MAIN	SR
Worst Pair	45	78	78	78
RL (dB)	10.0	9.7	12.8	14.1
Freq. (MHz)	2.5	2.6	91.8	75.3
Limit (dB)	17.0	17.0	10.4	11.2



Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	2.5GBASE-T	5GBASE-T
ATM-25	ATM-51	ATM-155
100VG-AnyLan	TR-4	TR-16 Active
TR-16 Passive		